



## LINUM



### Tekniske specifikationer

Power:	100-240V AC 50/60 Hz
PF:	0,90
Effektivitet:	90lm/W
SDCM:	3
Spredningsvinkel:	36°
Lysfordeling:	Direkte
Kapslingsklasse:	IP20
Isolationsklasse:	I
Forkobling:	On/off
Tilslutning:	Terminaler 3G2,5
Omgivelsestemperatur:	-20°C ~ +45°C
L80B50 (Ta 25°):	50.000 timer

### El tekniske data

Antal armaturer B16A:	48
Antal armaturer C16A:	48
Lækstrøm:	<0.75mA

### Produktinformationer

Montering:	Nedhængt
Materiale:	Aluminium
Farve:	Hvid RAL 9016 Sort RAL 9005
Pakningsstørrelse:	24 stk.

### Produktbeskrivelse

LINUM er en moderne slank pendel med mange anvendelsesmuligheder.

LINUM anvendes til diverse almene belysningsopgaver såsom:

- Kontorer
- Hoteller
- Lobbyer
- Receptioner
- Private hjem



# LINUM

Produkt nr.	Farve	Effekt/Watt	Lumen	Kelvin	RA	Materiale	Netto vægt (stk)
LI-18W-3-S	Sort	18	1.650	3000	>80	Alu	810g
LI-18W-3-S	Hvid	18	1.650	3000	>80	Alu	810g

