



## FRIGG



### Tekniske specifikationer

Power:	100V~277V AC 50/60 Hz
PF:	0,90
Effektivitet:	100lm/W
SDCM:	5
Spredningsvinkel:	60°
Lysfordeling:	Direkte
Kapslingsklasse:	IP66
IK klasse:	08
Isolationsklasse:	I
Forkobling:	On/off
Tilslutning:	Terminaler 3G2,5
Omgivelsestemperatur:	-40°C ~ +55°C
L80B50 (Ta 25°):	50.000 timer

### El tekniske data

	80W / 120W / 240W / 300W
Antal armaturer B10A:	5 / 4 / 2 / 1
Antal armaturer B16A:	9 / 6 / 3 / 2
Antal armaturer C10A:	5 / 4 / 2 / 1
Antal armaturer C16A:	9 / 6 / 3 / 2
Lækstrøm:	<0.75mA

### Produktinformationer

Montering:	Påbygning facade Mast
Materiale:	Aluminium
Cover:	Hærdet glas
Farve:	Coated gul
Pakningsstørrelse:	1 stk.

### Produktbeskrivelse

FRIGG er et udendørs ATEX certificeret LED armatur til Zone 2,22

Kontakt os for at få yderligere oplysninger om armaturet

### ATEX KLASSE

II 3G Ex nR II C T1 Gc  
II 2D Ex tb mc T1 Db IP66




# FRIGG

Produkt nr.	Effekt/Watt	Lumen	Kelvin	RA	Materiale	IK	Netto vægt (stk)
LLD-HRNT95 80	80	8.600	4000	>80	Aluminium	08	10.0kg
LLD-HRNT95 120	120	11.600	4000	>80	Aluminium	08	11.0kg
LLD-HRNT95 240	240	24.300	4000	>80	Aluminium	08	12.5kg
LLD-HRNT95 300	300	34.900	4000	>80	Aluminium	08	13.0kg


Produkter som ikke lagerføres

## Tilvalg

Gas	Støv	Kelvin
T4	T80°C	3000
T5	T95°C	5000
T6	T130°C	



HRNT95-80 / HRNT95-120



HRNT95-240 / HRNT95-300

